

## Air Conditioning and Refrigeration

### >B< MaxiPro Tube Compatibility Table Inch

>B< MaxiPro Tube Compatibility Table Inch														
>B< MaxiPro fitting size	Tube size Nominal OD		EN 12735-1 / EN 12735-2 - AS/ NZS 1571 - ASTM B280 - ASTM B88 - JIS H 3300											
			Nominal wall thickness											
	Inch	mm	0.025"	0.028" 22swg	0.030"	0.031" 0.032" 21swg	0.035" 0.036" 20swg	0.039" 0.040" 19swg	0.042"	0.045"	0.048" 18swg	0.049" 0.050"	0.055"	0.064" 0.065" 16swg
1/4	0.250"	6.35	■	●■	●■	●■	●■	●■						
3/8	0.375"	9.53		●■	●■	●■	●■	●■						
1/2	0.500"	12.70		●■	●■	●■	●■	●■			■	●■		
5/8	0.625"	15.88		●	●	●■	●■	●■		●	■	●■		
3/4	0.750"	19.05		●■		●■	●■	●■	●■	●■	●■	●■		
7/8	0.875"	22.23				●■	●■	●■		●■	■	■	■	●■
1	1.000"	25.40					■	■			■			■
1 1/8	1.125"	28.58					■	■			■	■		■
1 3/8	1.375"	34.93											■	■

- Coil lengths in annealed condition.
- Straight lengths in hard/half hard condition.

**Notes:**

- Ensure coil tubes are in round condition. Oval tubes should be re-rounded.
- Hardness tolerance as per approved standards in the table above.
- It is the engineer's responsibility to ensure that the tube selected is compatible with >B< MaxiPro and meets the operating pressure requirements of the system.

Title	Tool Compatibility Table - 32 kN Press Tool and Jaws Inch						
Issue	1	2	3	4	5	6	7
Date	01/09/2020	01/01/2021					